

Legacy Controls NOTICE

This article references our legacy Web Forms Web Viewing controls (WebImageViewer, WebAnnotationViewer, WebThumbnailViewer). It is preserved for archival purposes, but support strongly recommends using our modern HTML5 web controls: WebDocumentViewer, WebDocumentThumbnailer instead)

[INFO: WebDocumentViewer Whitepaper - Getting Started With Web Viewing](#)

Main Article Content

atalaWebAnnotationViewer

Although this function is public, it is not intended for users to create WebAnnotationViewers on the client side directly. The server side generated HTML is needed for this function to initialize.

Properties

Server Name	JavaScript Syntax : Return value	Description
Annotations[index]	getAnnotation(index : int): atalaAnnotation getAnnotation(layerindex : int, index : int) : atalaAnnotation	Gets the atalaAnnotation object at the given layer and item indexes, respectively.
Annotations	getAnnotations() : Array	Returns an array of atalaAnnotation objects that are on every layer in this control.
N/A	getAnnotationDataUrl() : string	Returns the url used to store the cached data file.
AuthorMode	getAuthorMode() : int	Gets a value that indicates how many annotations can be created with the mouse.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		Returns an int : 0:Unlimited 1:Single
AutoLinkThumbnailViewer	getAutoLinkThumbnailView : bool	Gets a value that indicates whether this control should automatically link events with the WebThumbnailViewer that is associated with this control
CurrentLayer	getCurrentLayer() : atalaLayer setCurrentLayer (value: atalaLayer) setCurrentLayer (value: int)	Gets or sets the current active layer in the control. This is primarily used to indicate which layer mouse events are handled on.
CurrentUserName	getCurrentUserName() : string	Returns a string that represents the current user name associated with this session. Note: This is not automatically populated, and as such, the CurrentUserName property must be set on the server side.
InteractMode	getInteractMode(): int setInteractMode (value : int)	Expected input: int from 0-2, 0:None 1:View 2:Edit
Annotations.Layers	getLayers() : Array	Returns an array of atalaLayer objects contained in this control.
N/A	getSelectedAnnotations() : Array	Returns an array of atalaAnnotation objects that have the Selected property set to true.

Inherited Properties from [atalaWebImageViewer](#)

Server Name	JavaScript Syntax : Return	Description
-------------	----------------------------	-------------

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

	value	
ClientID	ID() : string	Gets the server control identifier generated by ASP.NET.
N/A	Form() : object	Gets the form object that the Web server control is on.
AntialiasDisplay	getAntialiasDisplay() : int setAntialiasDisplay(value : int)	Gets or sets the quality of the scaled image. Expected input: AntialiasDisplayMode or int from 0-3, 0:None 1:ScaleToGray 2:ReductionOnly 3:Full
AutoZoom	getAutoZoom() : int setAutoZoom(value : int)	Gets or sets a value indicating how the image should be zoomed as the control is resized or the image size changes. This will override setZoom. For a one time zoom, see setZoomMode. Expected input: AutoZoomMode or int from 0-5, 0:None 1:BestFit 2:BestFitShrinkOnly 3:FitToWidth 4:FitToHeight 5:FitToImage
BackColor	getBackColor() : string setBackColor(value : string)	Gets or sets the background color of the Web server control. Expected input: string representing a hex value or exact color name: '#ACFF00'
BorderColor	getBorderColor() : string setBorderColor(value :	Gets or sets the border color of the Web server control.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

	string)	Expected input: string representing a hex value or exact color name: '#ACFF00'
BorderStyle	getBorderStyle() : string setBorderStyle(value : string)	Gets or sets the border style used for this Web server control. Expected input: string representing Style: '1px solid #FF9900'
BorderWidth	getBorderWidth() : int setBorderWidth(value : int)	Gets or sets the border width of the Web server control in pixels.
BrowserFormat	getBrowserFormat() : int	Gets the format of the images created for browser output. Returns an int : 0:Jpeg 1:Png 2:Gif 3:Auto
CachePath	getCachePath() : string	Gets the file path used for the file cache as specified in the Web.config file.
Caption	getCaption() : string setCaption(value : string)	Gets or sets a string used for creating a caption under the Web server control. HTML syntax is allowed. Note: This property is tied to a hidden input tag, so changing this value to HTML in JavaScript could cause problems if the page needs to PostBack.
Centered	getCentered() : bool setCentered(value : bool)	Gets or sets a value indicating if the image is centered when the image is smaller than the Web server control.
N/A	getDisplayImageUrl() :	Gets a url that will return the

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

	string	current viewable portion of the image. Often used for printing the current area of the image.
Font	getFont() : string setFont(value : string)	Gets or sets the font name associated with the Web server control. Expected input: string representing font name: 'Verdana'
ForeColor	getForeColor() : string setForeColor(value : string)	Gets or sets the foreground color (typically the color of the text) of the Web server control. Expected input: string representing a hex value or exact color name: '#ACFF00'
N/A	getFrameIndex() : int	Gets the index value used to open the current image. Note: If the image has been modified with a server side ApplyCommand, or has been opened from a method other than OpenUrl or a linked WebThumbnailViewer, this will always return 0.
Height	getHeight() : string setHeight(value : string)	Gets or sets the CSS height style property of the server control. Expected input: string representing style height: '320px'
ImageDisplayOrder	getImageDisplayOrder() : int	Gets the order that tiles are loaded.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		Returns an int : 0:Sequential 1:VisibleFirst 2:OnDemand
Image.Size	getImageSize() : ataSize	Gets the size, in pixels, of the current image.
N/A	getImageUrl() : string	Gets the currently loaded image url.
MouseTool	getMouseToolLeft() : int getMouseToolRight() : int setMouseTool (left: int , right: int)	Gets or sets the behavior of the mouse when interacting with the viewable area. Expected input: MouseToolType or int from 0-7, 0:None 1:Center 2:Selection 3:ZoomIn 4:ZoomOut 5:ZoomArea 6:Pan 7:PassThrough
MouseTool.Cursor	getMouseToolCursor() : int setMouseToolCursor (value : int)	Gets or sets the cursor used with the mouse tool. Expected input: MouseToolCursor or int from 0-8, 0:Auto 1:Arrow 2:Crosshair 3:Grab 4:Hand 5:Move 6:ZoomIn 7:ZoomOut 8:Custom Note: Currently, Grab is a CSS Extension supported by Mozilla based browsers only.
MouseTool.CustomCursor	getMouseToolCustomCursor : string setMouseToolCustomCursor : string)	Gets or sets a value that represents the custom CSS style used for the MouseTool. (value Expected input: string representing Style: 'wait' or 'url(MyCursor.cur)' Note: Url based CSS cursor styles may not work in all browsers.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

PathToResources	getPathToResources() : string	Gets the virtual path to where the image, script, and cursor files are located.
N/A	getReturnValue() : var	Gets the return value populated by the last successful RemoteInvoke.
ImagePosition	getScrollPosition() : ataPoint setScrollPosition(value : ataPoint)	Gets or sets the upper left image position in relation to the upper left corner of the Web server control. Negative values are expected. Expected input: ataPoint
ScrollBarVisibility	getScrollBarVisibility() : int	Gets the visibility of the scrollbars. Returns an int : 0:Dynamic 1:None 2:Always
Selection	getSelection() : Selection	Gets the Selection object of this Web server control.
TileSize	getTileSize() : ataSize	Gets the height and width of the tiles in pixels.
TitleBar	getTitleBar() : string setTitleBar(value : string)	Gets or sets a string used for a creating a title bar above the Web server control. HTML syntax is allowed. Note: This property is tied to a hidden input tag, so changing this value to HTML in JavaScript could cause problems if the page needs to PostBack.
ViewPortSize	getViewPortSize() : ataSize	Gets the size of the viewable area, excluding scroll bars.
Visibility	getVisibility() : string setVisibility(value : string)	Gets or sets a value that indicates whether the Web server control is hidden or

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		visible on the page. Expected input: string that is either 'hidden', 'visible', or 'inherit'. Note: 'inherit' will return VisibilityStyle.Visible on the server side.
Width	getWidth() : string setWidth(value : string)	Gets or sets the CSS width style property of the server control. Expected input: string representing style width: '200px'
Zoom	getZoom() : float setZoom(value : float)	Gets or sets the zoom level of the image in this Web server control.
ZoomInOutPercentage	getZoomInOutPercentage() : int setZoomInOutPercentage(value : int)	Gets or sets the percentage used to increase or decrease the zoom level when the zoom MouseTools are used.

Events

Server Name	JavaScript Syntax	Description
Annotation Events	Note: These events only pertain to the underlying atalaAnnotation objects.	
N/A	AnnotationChanged = function(e)	Fires when an atalaAnnotation has changed. Passes an AnnotationEvent object.
N/A	AnnotationChanging = function(e)	Fires while an atalaAnnotation is changing. Passes an AnnotationEvent object.
N/A	AnnotationClicked = function(e)	Fires when an atalaAnnotation is clicked

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		with the left mouse button. Passes an AnnotationEvent object.
N/A	AnnotationCreated = function(e)	Fires when an atalaAnnotation is created with the mouse. Passes an AnnotationEvent object.
N/A	AnnotationDoubleClicked = function(e)	Fires when an atalaAnnotation is double-clicked with the left mouse button. Passes an AnnotationEvent object.
N/A	AnnotationMouseDown = function(e)	Fires when a mouse button is pressed down on an atalaAnnotation. Passes an AnnotationEvent object.
N/A	AnnotationMouseDownLeft = function(e)	Fires when the left mouse button is pressed down on an atalaAnnotation. Passes an AnnotationEvent object.
N/A	AnnotationMouseDownRight = function(e)	Fires when the right mouse button is pressed down on an atalaAnnotation. Passes an AnnotationEvent object.
N/A	AnnotationMouseMove = function(e)	Fires when the mouse cursor moves over an atalaAnnotation. Passes an AnnotationEvent object.
N/A	AnnotationMouseOut = function(e)	Fires when the mouse cursor leaves an atalaAnnotation's area. Passes an AnnotationEvent object.
N/A	AnnotationMouseOver = function(e)	Fires when the mouse cursor enters an atalaAnnotation's area. Passes an AnnotationEvent object.
N/A	AnnotationMouseUp = function(e)	Fires when a mouse button is released on an

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		atalaAnnotation. Passes an AnnotationEvent object.
N/A	AnnotationRightClicked = function(e)	Fires when an atalaAnnotation is right clicked. Passes an AnnotationEvent object.
N/A	AnnotationsChanged = function(e)	Fires when the z-order of atalaAnnotations has changed. Passes an AnnotationEvent object.
Layer Events	Note: These events only pertain to the underlying atalaLayer objects.	
N/A	CurrentLayerChanged = function(e)	Fires when the current atalaLayer object has been changed to a different atalaLayer. Passes an AnnotationEvent object.
N/A	LayerChanged = function(e)	Fires when an atalaLayer has changed. Passes an AnnotationEvent object.
N/A	LayersChanged = function(e)	Fires when the z-order of atalaLayers has changed. Passes an AnnotationEvent object.

Events inherited from [atalaWebImageViewer](#)

Server Name	JavaScript Syntax	Description
N/A	AntialiasDisplayChanged = function()	Fires when the AntialiasDisplay property has changed.
N/A	AutoZoomChanged = function()	Fires when the AutoZoom property has changed.
N/A	BackColorChanged = function()	Fires when the BackColor property has changed.
N/A	BorderColorChanged = function()	Fires when the BorderColor property has changed.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

N/A	BorderStyleChanged = function()	Fires when the BorderStyle property has changed.
N/A	BorderWidthChanged = function()	Fires when the BorderWidth property has changed.
N/A	CaptionChanged = function()	Fires when the Caption property has changed.
CenteredChanged	CenteredChanged = function()	Fires when the Centered property has changed.
N/A	FontChanged = function()	Fires when the Font property has changed.
N/A	ForeColorChanged = function()	Fires when the ForeColor property has changed.
ImageChanged	ImageChanged = function()	Fires when the Image has changed.
N/A	ImageSizeChanged = function()	Fires when the Image changes size.
N/A	MouseToolChanged = function()	Fires when the MouseTool property has changed.
RemoteInvoked	RemoteInvoked = function()	Fires when the RemoteInvoke function is called.
ImagePositionChanged	ScrollPositionChanged = function()	Fires when the ScrollPosition has changed
SelectionChanged	SelectionChanged = function()	Fires when the Selection has changed.
N/A	SizeChanged = function()	Fires when the Size property has changed.
N/A	TitleBarChanged = function()	Fires when the TitleBar property has changed.
N/A	VisibilityChanged = function()	Fires when the Visibility property has changed.
N/A	ZoomChanged = function()	Fires when the Zoom property has changed.
N/A	ZoomInOutPercentageChanged = function()	Fires when the ZoomInOutPercentage property has changed.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

Mouse Events	Note: All of these events pertain to the underlying image only, and attempt to pass a ImageMouseEvent object to the function.	
N/A	Clicked = function(e)	Fires when the image is clicked. Passes an ImageMouseEvent object.
N/A	DoubleClicked = function(e)	Fires when the image is double clicked. Passes an ImageMouseEvent object.
N/A	MouseDown = function(e)	Fires when a mouse button is pressed down on the image. Passes an ImageMouseEvent object.
N/A	MouseDownLeft = function(e)	Fires when the when the left mouse button is pressed down. Passes an ImageMouseEvent object.
N/A	MouseDownRight = function(e)	Fires when the when the right mouse button is pressed down. Passes an ImageMouseEvent object.
N/A	MouseMove = function(e)	Fires when the mouse cursor moves over the image. Passes an ImageMouseEvent object.
N/A	MouseOut = function(e)	Fires when the mouse cursor leaves the image area. Passes an ImageMouseEvent object.
N/A	MouseOver = function(e)	Fires when the mouse cursor enters the image area. Passes an ImageMouseEvent object.
N/A	MouseUp = function(e)	Fires when a mouse button is released on the image. Passes an ImageMouseEvent object.

N/A	RightClicked = function(e)	Fires when the image is right clicked. Passes an ImageMouseEvent object.
Key Events	Note: The control must have focus for these events to fire. You can programmatically set focus to this control by calling Focus() . These events also attempt to pass a ImageKeyEvent object to the function.	
N/A	KeyDown = function(e)	Fires when a key is pressed down, if the control has focus. Passes an ImageKeyEvent object.
N/A	KeyUp = function(e)	Fires when a key is released, if the control has focus. Passes an ImageKeyEvent object.
N/A	KeyPress = function(e)	Fires when a key is pressed down, and then released, if the control has focus. Passes an ImageKeyEvent object.

Methods

Server Name	JavaScript Syntax : Return value	Description
Annotations.Layers.Add	AddLayer (layer: atalaLayer) : bool	Adds the given atalaLayer to this control. Returns true on success, false otherwise.
N/A	Clear ()	Clears all annotations, all layers, and the image contained in this control.
Annotations.Layers.Clear	ClearAnnotations ()	Clears all annotations and all layers contained in this control.
N/A	CountAnnotations () : int	Returns an int of the total count of all annotations on all layers in this control.
Annotations.Layers.Count	CountLayers () : int	Returns an int of the count of all layers in this control.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

N/A	CreateAnnotation(type: string) : atalaAnnotation CreateAnnotation(type: string, name: string) : atalaAnnotation	Creates and returns an atalaAnnotation from the object type string specified. The string must represent an object type that inherits from Atalasoft.Annotate.AnnotationData on the server side. Expected input: string representing AnnotationData: 'EllipseData' or 'RectangleData', string representing the name of a DefaultAnnotation created on the server side. Note: The atalaAnnotation returned must be added to an atalaLayer by using InsertAnnotation or it will be created by drawing it with the mouse (if the current AnnotationInteractMode allows)
N/A	CreateLayer() : atalaLayer	Creates and returns an atalaLayer object. Note: The atalaLayer returned must be added using AddLayer or it (including child annotations) will not be visible.
N/A	DeleteAnnotation(zindex: int) : bool	Deletes the atalaAnnotation at the given z-index from the CurrentLayer. Returns true on success, false otherwise.
N/A	DeleteAnnotations(anns: Array) : bool	Deletes an Array of atalaAnnotations from their

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		parent atalaLayers . Returns true on success, false otherwise.
N/A	DeselectAll()	Sets the Selected property of all atalaAnnotations on all atalaLayers to false, and hides their grips.
Annotations.CurrentLayer.InsertAnnotation	InsertAnnotation (ann: atalaAnnotation , zindex: int) : bool	Inserts the given atalaAnnotation into the CurrentLayer , at the given z-index, and automatically removes it from it's previous parent object (if any). Returns true on success, false otherwise.
LoadAnnotationDataUrl	LoadAnnotations (url: string)	Loads annotation data from a URL or virtual path.
N/A	SelectAll()	Sets the Selected property of all atalaAnnotations on all atalaLayers to true, and shows their grips.

Methods Inherited from [atalaWebImageViewer](#)

Server Name	JavaScript Syntax	Description
N/A	ClearImage()	Clears the image from client side only, used to return to a blank state.
N/A	Focus()	Puts focus on the WebImageViewer, used to enable key events.
N/A	Invalidate()	Forces the WebImageViewer to re-position child objects.
OpenUrl	OpenUrl (url: string) OpenUrl (url: string, index: int)	Opens an image into the WebImageViewer control from a URL or virtual path, and frame index.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		Note: This function is asynchronous. If any code needs to be executed after this call, it should be placed in the ImageChanged event handler.
N/A	PauseRefresh()	Pauses UI updates for this control until ResumeRefresh is called. Pauses and Refreshes are nestable. The update happens when an equal number of ResumeRefresh and PauseRefresh calls are made.
Print	Print()	Prints the current image using javascript client code.
Redo	Redo()	Re-does an undo.
Invoke	RemoteInvoke (mthd : string) RemoteInvoke (mthd : string , args : Array)	Remotely invokes a server side method with the array of arguments. Note: This function is asynchronous. If any code needs to be executed after this call, it should be placed in the RemoteInvoked event handler.
N/A	ResumeRefresh()	Resumes paused UI updates for this control. Pauses and Refreshes are nestable. The update happens when an equal number of ResumeRefresh and PauseRefresh calls are made.
N/A	ScrollBy (dx : int , dy : int)	Scrolls the viewer by the given values.
N/A	ScrollTo (x: int , y: int)	Scrolls the viewer to the given coordinates.

N/A	setZoomMode (value : int)	Zoom the image once, according to the given AutoZoomMode . Expected input: AutoZoomMode or int from 0-5, 0:None 1:BestFit 2:BestFitShrinkOnly 3:FitToWidth 4:FitToHeight 5:FitToImage
Undo	Undo ()	Reverts the image back to the previously cached image. Note: This function is limited to Image changes only. The number of available undos relies on the server side CacheLevels property of the control.
Update	Update ()	Forces the current image to be cached and updates the viewable area.

AnnotationEvent

This object is based on the browser's mouse event object, if it pertains to a mouse event. The following properties are in addition to the properties that are specified by each individual browser.

Usage:

JavaScript

```
/* You will need a WebAnnotationViewer and a reference to ClientTools.js before this snippet.
 * This reference is automatically added to the page inline with the WebControls, * so placing
 * this snippet below the WebAnnotationViewer control will be sufficient. */
Atalasoft.Utils.InitClientScript(BindAnnotationEvents); function BindAnnotationEvents(){
```

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

```
WebAnnotationViewer1.AnnotationDoubleClicked = AnnotationEventExample;  
WebAnnotationViewer1.AnnotationRightClicked = AnnotationEventExample; } // This simple  
example alerts the user when an annotation is double or right clicked. function  
AnnotationEventExample(e){ var pos = Atalasoftware.Utils.getMousePosition(e); alert('Event fired  
on annotation at position: ' + pos.X + 'x' + pos.Y); }
```

Properties

Server Name	JavaScript Syntax : Return value	Description
N/A	annotation : atalaAnnotation	The atalaAnnotation object that this event was fired from, if any. Returns null if this event was fired from a layer.
N/A	layer : atalaLayer	The atalaLayer object that this event was fired from, if any. Returns null if this event was fired from an annotation.

atalaLayer

This object represents the client side JavaScript version of an Atalasoftware.Annotations.LayerAnnotation object.

Properties

Server Name	JavaScript Syntax : Return value	Description
LayerAnnotation.Items	getAnnotations() : Array	Returns an array of annotations that are contained in this layer.
N/A	getLayerIndex() : int	Returns an integer that

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		corresponds with the array index of this layer.
LayerAnnotation.Visible	getVisibility() : string setVisibility(value : string)	Gets or sets a value that indicates whether the layer and child elements are hidden or visible in the control. Expected input: string that is either "hidden" or "visible"

Methods

Server Name	JavaScript Syntax : Return value	Description
LayerAnnotation.Items.Add	Add() : bool	Adds the given atalaAnnotation to the annotation array at the top most z-order. Returns true if the add succeeded, false otherwise.
N/A	Delete() : bool	Deletes the atalaAnnotation at the given index, and disposes of DOM objects. Returns true on success, false on failure.
LayerAnnotation.Items.Insert	Insert() : bool	Inserts the given atalaAnnotation into the annotation array at the given index. Returns true if the insert succeeded, false otherwise.

Events

Server Name	JavaScript Syntax	Description
N/A	Changed = function(e)	Fires when the layer has changed.
N/A	ItemsChanged = function(e)	Fires when child annotations have changed z-order.

atalaAnnotation

This object represents the client side JavaScript version of an Atalasoft.Annotations.AnnotationUI object.

Properties

Server Name	JavaScript Syntax : Return value	Description
AnnotationUI.AspectRatio	getAspectRatio() : float setAspectRatio(value : float)	Gets or sets a value that indicates the aspect ratio of this annotation. A value of zero will not maintain any aspect ratio.
N/A	setEditorHtml(value : string)	Sets the innerHTML of the DOM object that is used to edit the annotation.
N/A	getEditorObject() : object	Gets the DOM object that is used to edit the annotation.
AnnotationUI.Height	getHeight() : int setHeight(value : int)	Gets or sets the height of the annotation.
AnnotationUI.Movable	getMovable() : bool setMovable(value : bool)	Gets or sets a value that indicates whether the annotation can be moved with the mouse.
	getParent() : atalaLayer	Gets the parent object of this annotation.
AnnotationUI.Position	getPosition() : atalaPoint setPosition(value : atalaPoint)	Gets or sets the position of the annotation.
	getRectangle() : atalaRectangle setRectangle(value : atalaRectangle)	Gets or sets the size and position of this annotation.
AnnotationUI.Resizable	getResizable() : bool	Gets or sets a value that

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

	setResizable (value : bool)	indicates whether the annotation can be resized with the mouse.
	getSize () : atalaSize setSize (value : atalaSize)	Gets or sets the size of this annotation.
AnnotationUI.Selected	getSelected () : bool setSelected (value : bool)	Gets or sets a value that indicates whether the annotation is selected.
AnnotationUI.Tooltip	getToolTip () : string setToolTip (value : string)	Gets or sets the tooltip that is displayed when the mouse is moved over this annotation.
	getType () : string	Gets the AnnotationData type for this annotation.
AnnotationUI.Visible	getVisibility () : string setVisibility (value : string)	Gets or sets a value that indicates whether the annotation is hidden or visible. Expected input: string that is either "hidden" or "visible"
AnnotationUI.Width	getWidth () : int setWidth (value : int)	Gets or sets the width of the annotation.
N/A	getZIndex () : int	Gets the z-index of this annotation.

Methods

Server Name	JavaScript Syntax	Description
N/A	HideEditor ()	Hides the editor for this annotation, if there is one.
N/A	ShowEditor ()	Shows the editor for this annotation, if there is one.
N/A	Synchronize ()	Synchronizes the annotation bounds with underlying data. This should only be used if the data object is being

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

		changed directly.
N/A	Update()	Synchronizes the client-side annotation data with the server-side annotation data, and requests a new image from the server.
N/A	Repaint()	Sends a request to the server for a new annotation image.

Events

Server Name	JavaScript Syntax	Description
N/A	Changed = function(e)	Fires when the annotation has finished being modified.
N/A	Changing = function(e)	Fires while the annotation is being modified through mouse movement.
N/A	Clicked = function(e)	Fires when the annotation is clicked.
N/A	DoubleClicked = function(e)	Fires when the annotation is double clicked.
N/A	MouseDown = function(e)	Fires when a mouse button is pressed down on the annotation.
N/A	MouseDownLeft = function(e)	Fires when the left mouse button is pressed down on the annotation.
N/A	MouseDownRight = function(e)	Fires when the right mouse button is pressed down on the annotation.
N/A	MouseMove = function(e)	Fires when the mouse cursor moves over the annotation.
N/A	MouseOut = function(e)	Fires when the mouse cursor leaves the annotation area.

INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

N/A	MouseOver = function(e)	Fires when the mouse cursor enters the annotation area.
N/A	MouseUp = function(e)	Fires when a mouse button is released on the annotation.
N/A	RightClicked = function(e)	Fires when the annotation is right clicked.
N/A	Selected = function(e)	Fires when the annotation is selected.

Original Article:

Q10357 - INFO: WebAnnotationViewer - JavaScript API Reference (Legacy Web Controls)

Atalasoft Knowledge Base

<https://www.atalasoft.com/kb2/KB/50130/INFO-WebAnnotationViewer-JavaScript-...>